

PDU Technology Specification

Date: 06/17/2016

NO.:

| | | | |
|--|---|--|--|
| Customer | | RoHS | |
| | | Yes | |
| Product Name | | Customer's Code | |
| Designated Power Distribution Unit for Cabinet | | | |
| Part Number | | Picture Code | |
| | | | |
| No. | Item | Detailed Description | |
| 1 | Product Series | | |
| 2 | Socket Type | BS1363 45degree[5];IEC320 C19 Socket(Single 1)(Right)[3];Single IEC320 C13 | |
| 3 | Socket Quantity | 24 | |
| 4 | Power Input | Left end single input (bottom entry) | |
| 5 | Bracket Install | Inverse installation | |
| 6 | Cable with plug | IEC60309 plug (32A 2P+E) | |
| 7 | Control Function | No controlling function | |
| 8 | Protection Function | No protecting function | |
| 9 | Case | Black | |
| 10 | Cable Specification | 3 x 6.0 mm ² x 3M | |
| 11 | Product Size | L x W x H = 1238.5 x 44.4 x 62 mm | |
| 12 | Mounting Length | 1210.5 mm | |
| 13 | Case Length | 1182.5 mm | |
| 14 | PDU Exponent | 2. 033 | |
| 15 | Fittings | 2pcs $\phi 6 \times 16$ mm cross bolt, 2pcs M6 float nut, PDU manual | |
| 16 | Product Label | Product Name | Designated Power Distribution Unit for Cabinet |
| | | Specification Model | |
| | | Rating voltage | 250VAC 50/60Hz |
| | | Rating Current | 32A |
| | | Max. Current | |
| | | Max. Power | 8000W |
| | | Safety Authentication | CE |
| | | Logo | |
| | | Producer | |
| No. | Add-In | | |
| 1 | Socket assemble | NO | |
| 2 | Interior Connection Wire | 2.5 mm ² (14AWG) | |
| 3 | Interior Connection Style | Group connection | |
| 4 | Fix the Cable | Cable clamp(19) | |
| 5 | Module Assemble (from left to right) | Pls refer to the drawing | |
| 6 | Others | NO | |
| Made by: | | Customer confirm: | Check: Authorize: |

This technology specification is for: design product for customer and confirm customer's requirements, and is also the basic gist for arranging production.

PDU Technology Specification

Date: 06/17/2016

NO.: HKLU03A1606071

Preview



IEC60309 plug (32A 2P+E)

| | | | | |
|--|--|------------|-----------------|--|
| DIMENSION AND TOLERANCES (Unit: mm) Length:1238.5 Mounting length: 1210.5 Width: 44.4 Case length: 1182.5 Height: 62 case tolerance: \pm 1.0 | | | | |
| | | | Customer | |
| | | | Product name | Designated Power Distribution Unit for Cabinet |
| | | | Part number | |
| DRAWN | | 06/17/2016 | Customer's code | |
| CHK'D | | | Drawing number | |
| APP'D | | | Edition number | |